



Copyright 2016, Azuradisc Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Azuradisc products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Azuradisc, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: Identification

Product Identifier

Product Name Policool 5.0

Product form: Liquid

Color: White

Odor: No data available

Recommended Use: Liquid Abrasive product to polish polycarbonate and other substrates.

Supplier's details

MANUFACTURER

Azuradisc, Inc.

ADDRESS:

7307 South 89th

Place

Mesa, AZ 85212

TELEPHONE: 480-827-8786

Toll Free telephone number 1-800-933-4923 Emergency Telephone: Dial 911 in the United States.

SECTION 2: Hazards identification

WARNING!

Causes eye irritation. May cause skin irritation.

Potential Health Effects

Inhalation: In high concentrations, vapors may be irritating to the respiratory system.

Eye Contact: Causes eye irritation. Exposed individuals may experience eye tearing, redness, and discomfort.

Skin Contact: May cause skin irritation. **Ingestion:** May cause discomfort if swallowed. **Chronic Health Effects:** No data available.

Target Organ(s): | Eye | Skin | Respiratory system | Lung |

Potential Physical / Chemical Effects: This product is not flammable.

OSHA Regulatory Status: This product is hazardous according to OSHA 29CFR 1910.1200.

Environment: The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

SECTION 3: Composition/information on ingredients

Ingredients

| Chemical Name | CAS-No. | Concentration* |
|--|------------|----------------|
| Water | 7732-18-5 | >90 % |
| † Aluminum oxide | 1344-28-1 | 8 - 10% |
| † Aluminum nitrate | 7784-27-2 | 1 - 5% |
| † Distillates (petroleum), hydrotreated light naphthenic | 64742-53-6 | 0.05 - 0.2% |
| Silicone Oil | 94363-18-5 | <1 % |
| Surfactants | 9088-43-1 | <1 % |

* All concentrations are in percent estimate by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

† This chemical is hazardous according to OSHA/WHMIS criteria.

**SECTION 4: First aid measures**

Inhalation: Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Flush thoroughly with water. If irritation occurs, get medical assistance. Get medical attention.

Skin Contact: Flush skin thoroughly with water. If irritation occurs, get medical assistance.

Ingestion: Rinse mouth thoroughly. Get medical attention if any discomfort occurs.

SECTION 5: Firefighting measures

Extinguishing Media: Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable Extinguishing Media: None.

Special Fire Fighting Procedures: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Unusual Fire & Explosion Hazards: None known.

Hazardous Combustion Products: Alumina compounds, Nitrogen Oxides

Protective Measures: Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

Personal Precautions: Avoid contact with eyes and prolonged skin contact. Wear appropriate personal protective equipment. See Section 8 of the Safety Data Sheet for Personal Protective Equipment.

Spill Cleanup Methods: Absorb in vermiculite, dry sand or earth and place into containers. Collect and dispose of Spillage as indicated in section 13 of the Safety Data Sheet.

Environmental Precautions: Avoid discharge into drains, water courses or onto the ground.

Notification Procedures: Inform authorities if large amounts are involved.

SECTION 7: Handling and storage

Handling: Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Use only in Well-ventilated areas. Observe good industrial hygiene practices.

Storage: Store in a cool and well-ventilated place. Keep container closed when not in use. Store away from incompatible materials

SECTION 8: Exposure controls/personal protection**Exposure Limits:**

| Chemical Name | Source | Type | Exposure Limits | Notes |
|--|---------------------------|------|--------------------------------|-------|
| Aluminum oxide | CA. Alberta OELs | TWA | 10 mg/m ³ | |
| Aluminum oxide (Dust.) | CA. Ontario OELs | TWA | 10 mg/m ³ | |
| Aluminum oxide (Total dust.) | CA. Ontario OELs | TWA | 10 mg/m ³ | |
| Aluminum oxide | MEX. OELs | TWA | 10 mg/m ³ | |
| Aluminum oxide (Respirable fraction.) | US. OSHA Z-1 PEL | TWA | 5 mg/m ³ | |
| Aluminum nitrate | CA. Alberta OELs | TWA | 2 mg/m ³ | as Al |
| Aluminum nitrate | CA. British Columbia OELs | TWA | 2 mg/m ³ | as Al |
| Aluminum nitrate | CA. Quebec OELs | TWA | 2 mg/m ³ | as Al |
| Aluminum nitrate | MEX. OELs | TWA | 2 mg/m ³ | |
| Distillates (petroleum), hydrotreated light naphthenic | CA. Ontario OELs | TWA | 1600 mg/m ³ | |
| Distillates (petroleum), hydrotreated light naphthenic | US. OSHA Z-1 PEL | TWA | 2000 mg/m ³ 500 ppm | |



Engineering Controls: Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of spray. Observe good industrial hygiene practices.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: High-efficiency particulate respirator.

Eye Protection: Wear approved safety goggles.

Hand Protection: Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

Skin Protection: Apron and long sleeves are recommended.

Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental Exposure Controls: Environmental manager must be informed of all major spillages.

SECTION 9: Physical and chemical properties

Color: White

Odor: No data available.

Odor Threshold: No data available.

Physical State: Liquid

pH: 2.4 - 3.5

Melting Point: Not applicable. **Freezing**

Point: No data available. **Boiling Point:**

100°C (212°F) **Flash Point:** No data available.

Evaporation Rate: 1

Flammability Limit - Upper (%): No data available.

Flammability Limit - Lower (%): No data available. **Vapor**

Pressure: 3.1 kPa (@ 25°C)

Vapor Density (Air=1): 1.1 - 1.2

Specific Gravity: 1.17 (@ 25°C)

Solubility in Water: Completely soluble in water

Solubility (Other): Not applicable.

Partition Coefficient (n-Octanol/water): No data available.

Auto ignition Temperature: No data available.

Decomposition Temperature: No data available.

Viscosity: 40 cps

SECTION 10: Stability and reactivity

Stability: Stable under normal temperature conditions

Conditions to Avoid: Excessive heat. Freezing.

Incompatible Materials: Strong bases.

Hazardous Decomposition Products:

At Elevated Temperatures: Alumina compounds, Nitrogen Oxides

Possibility of Hazardous Reactions: Will not occur.



SECTION 11: Toxicological information

| Chemical Name | Test Results |
|--|----------------------------------|
| Aluminum nitrate | Oral LD50 (Rat): 3671 mg/kg |
| Distillates (petroleum), hydrotreated light naphthenic | Inhalation LC50 (Rat): 2.81 mg/l |

Listed Carcinogens: None.

Product Information Acute Toxicity:

Test Results: No test data available for the product.

Other Acute: Causes eye irritation. May cause skin irritation.

Chronic Toxicity: No data available.

SECTION 12: Ecological information

Eco toxicity: The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Mobility: The product is soluble in water.

Persistence and Degradability: No data available.

Bioaccumulation Potential: No data available.

SECTION 13: Disposal considerations

General Information: Dispose of waste and residues in accordance with local authority requirements.

Disposal Methods: Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

No Special Requirements

DOT Not regulated.

TDG Not regulated.

IATA Not regulated.

IMDG Not regulated.



SECTION 15: Regulatory information

Canadian Controlled Products Regulations: This product has been classified according to the hazard criteria of the Canadian Controlled Products Regulations, Section 33, and the MSDS contains all required information.

WHMIS Classification: D2B

Inventory Status:

This product or all components are listed or exempt from listing on the following inventory: **DSL, TSCA**

US Regulations

CERCLA Hazardous Substance List (40 CFR 302.4): **Not regulated.**

SARA Title III

Section 302 Extremely Hazardous Substances (40 CFR 355, Appendix A): Not regulated.

Section 311/312 (40 CFR 370):

| | |
|---|-------------------|
| X | Acute (Immediate) |
| | Chronic (Delayed) |
| | Fire |
| | Reactive |

Section 313 Toxic Release Inventory (40 CFR 372):

| Chemical Name | CAS-No. | Reporting threshold for other users | Reporting threshold for manufacturing and processing |
|------------------|-----------|-------------------------------------|--|
| Aluminum nitrate | 7784-27-2 | 10000 lbs. | 25000 lbs. |
| Aluminum oxide | 1344-28-1 | 10000 lbs. | 25000 lbs. |

For reporting purposes: the De Minimis Concentration for a toxic chemical in a mixture is 0.1% for carcinogens as defined in 29 CFR 1910.1200(d)(4) or 1% for others.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Not regulated.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3): Not regulated.

Drug Enforcement Act: Not regulated.

TSCA

TSCA Section 4(a) Final Test Rules & Testing Consent Orders: Not regulated.

TSCA Section 5(a) (2) Final Significant New Use Rules (SNURs) (40CFR 721, Subpt. E): Not regulated.

TSCA Section 5(e) PMN-Substance Consent Orders: Not regulated.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

State Regulations

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): Not regulated.

Massachusetts Right-To-Know List: Aluminum oxide; Distillates (petroleum), hydro treated light naphthenic

Michigan Critical Materials List (Michigan Natural Resources and Environmental Protection Act (Act. 451 of 1994)):

Not regulated.

Minnesota Hazardous Substances List: Aluminum oxide; Aluminum nitrate

New Jersey Right-To-Know List: Aluminum oxide; Aluminum nitrate

Pennsylvania Right-To-Know List: Aluminum oxide; Aluminum nitrate

Rhode Island Right-To-Know List: Aluminum oxide

**SECTION 16: Other information****NFPA Hazard Classification**

| | Health Hazard | Fire Hazard | Instability | Special Hazard |
|-------------|---------------|-------------|-------------|----------------|
| NFPA | 1 | 0 | 0 | -- |

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe

NFPA Label colored diamond code: Blue - Health; Red - Flammability; Yellow - Instability; White - Special Hazards

| | Health Hazard | FLAMIBILITY | PHYSICAL HAZARD | PERSONAL PROTECTION |
|-------------|---------------|-------------|-----------------|---------------------|
| HMIS | 1 | 0 | 0 | X |

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; - Severe Personal Protection codes: X - Specialized Handling

HMIS Label colored bar code: Blue - Health; Red - Flammability; Orange - Physical Hazards; White - Special

Issue Date: September 20, 2016

Supersedes all previous versions

Date: SDS

DISCLAIMER: The information in this SAFETY DATA Sheet (SDS) is believed to be correct as of the date issued. Azuradisc **MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.** User is responsible for determining whether the Azuradisc product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Azuradisc product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Azuradisc product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Azuradisc provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Azuradisc makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information available directly from Azuradisc Inc.