



Copyright 2016, Azuradisc Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Azuradisc products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Azuradisc, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: Identification

Product Identifier

Product Name Formula 3 Polishing Compound

Product form: Liquid

Color: Grey

Odor: Aliphatic solvent

Recommended Use: Liquid Abrasive product to polish polycarbonate and other substrates.

Supplier's details

MANUFACTURER

Azuradisc, Inc.

ADDRESS:

7307 South 89th
Place
Mesa, AZ 85212

TELEPHONE: 480-827-8786

Toll Free telephone number 1-800-933-4923 Emergency Telephone: Dial 911 in the United States.

SECTION 2: Hazards identification

WARNING!

Causes eye irritation. May cause skin irritation.

Potential Health Effects

Inhalation: In high concentrations, vapors may be irritating to the respiratory system.

Eye Contact: Causes eye irritation. Exposed individuals may experience eye tearing, redness, and discomfort.

Skin Contact: May cause skin irritation. **Ingestion:** May cause discomfort if swallowed. **Chronic Health Effects:** No data available.

Target Organ(s): | Eye | Skin | Respiratory system | Lung |

Potential Physical / Chemical Effects: This product is not flammable.

OSHA Regulatory Status: This product is hazardous according to OSHA 29CFR 1910.1200.

Environment: The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

SECTION 3: Composition/information on ingredients

Ingredients

Chemical Name	CAS-No.	Concentration*
Aliphatic Hydrocarbon Mixture	68551-19-9	90
Remaining components are Proprietary, non-hazardous, and/or present at amounts below reportable limits.		10

* All concentrations are in percent estimate by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

† This chemical is hazardous according to OSHA/WHMIS criteria.

**SECTION 4: First aid measures**

Inhalation: Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Flush thoroughly with water. If irritation occurs, get medical assistance. Get medical attention.

Skin Contact: Flush skin thoroughly with water. If irritation occurs, get medical assistance.

Ingestion: Rinse mouth thoroughly. Get medical attention if any discomfort occurs.

SECTION 5: Firefighting measures

Extinguishing Media: Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable Extinguishing Media: None.

Special Fire Fighting Procedures: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Unusual Fire & Explosion Hazards: None known.

Hazardous Combustion Products: Alumina compounds, Nitrogen Oxides

Protective Measures: Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

Personal Precautions: Avoid contact with eyes and prolonged skin contact. Wear appropriate personal protective equipment. See Section 8 of the Safety Data Sheet for Personal Protective Equipment.

Spill Cleanup Methods: Absorb in vermiculite, dry sand or earth and place into containers. Collect and dispose of Spillage as indicated in section 13 of the Safety Data Sheet.

Environmental Precautions: Avoid discharge into drains, water courses or onto the ground.

Notification Procedures: Inform authorities if large amounts are involved.

SECTION 7: Handling and storage

Handling: Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Use only in Well-ventilated areas. Observe good industrial hygiene practices.

Storage: Store in a cool and well-ventilated place. Keep container closed when not in use. Store away from incompatible materials

SECTION 8: Exposure controls/personal protection**Exposure Limits:**

Chemical Name	Source	Type	Exposure Limits	Notes
Aluminum oxide	CA. Alberta OELs	TWA	10 mg/m ³	
Aluminum oxide (Dust.)	CA. Ontario OELs	TWA	10 mg/m ³	
Aluminum oxide (Total dust.)	CA. Ontario OELs	TWA	10 mg/m ³	
Aluminum oxide	MEX. OELs	TWA	10 mg/m ³	
Aluminum oxide (Respirable fraction.)	US. OSHA Z-1 PEL	TWA	5 mg/m ³	
Aluminum nitrate	CA. Alberta OELs	TWA	2 mg/m ³	as Al
Aluminum nitrate	CA. British Columbia OELs	TWA	2 mg/m ³	as Al
Aluminum nitrate	CA. Quebec OELs	TWA	2 mg/m ³	as Al
Aluminum nitrate	MEX. OELs	TWA	2 mg/m ³	
Distillates (petroleum), hydrotreated light naphthenic	CA. Ontario OELs	TWA	1600 mg/m ³	
Distillates (petroleum), hydrotreated light naphthenic	US. OSHA Z-1 PEL	TWA	2000 mg/m ³ 500 ppm	



Engineering Controls: Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of spray. Observe good industrial hygiene practices.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: High-efficiency particulate respirator.

Eye Protection: Wear approved safety goggles.

Hand Protection: Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

Skin Protection: Apron and long sleeves are recommended.

Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental Exposure Controls: Environmental manager must be informed of all major spillages.

SECTION 9: Physical and chemical properties

Color: Grey

Odor: Aliphatic solvent

Odor Threshold: No data available.

Physical State: Liquid Emulsion

pH: 7.2

Melting Point: 32°F

Freezing Point: No data available.

Boiling Point: 100°C (212°F)

Flash Point: No data available.

Evaporation Rate: 1

Flammability Limit - Upper (%): No data available.

Flammability Limit - Lower (%): No data available.

Vapor Pressure: .12 mmHg

Vapor Density (Air=1): >3

Specific Gravity: 1.10 (@ 25°C)

Solubility in Water: partially dispersible

Solubility (Other): Not applicable.

Partition Coefficient (n-Octanol/water): No data available.

Auto ignition Temperature: >89°C (192°F) TCC 471°C (880°F)

Decomposition Temperature: No data available.

Viscosity: 1000 cst

SECTION 10: Stability and reactivity

Stability: Stable under normal temperature conditions

Conditions to Avoid: Excessive heat. Freezing.

Incompatible Materials: Strong bases.

Hazardous Decomposition Products:

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion

Possibility of Hazardous Reactions: Keep away from extreme heat, Strong Acids, Alkalis and Oxidizers such as Chlorine, other Halogens, Hydrogen Peroxide and Oxygen No substances are readily identifiable from composition but no degradation data is available.



SECTION 11: Toxicological information

NATURE OF HAZARD AND TOXICITY INFORMATION

Prolonged or repeated skin contact with this product tends to remove skin oils, possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

SECTION 12: Ecological information

Eco toxicity: Do not discharge this product into public waters or waterways unless authorized by a National Pollution Discharge Elimination System (NPDES) permit issued by the Environmental Protection Agency (EPA).

Mobility: The product is partially dispersible in water.

Persistence and Degradability: No data available.

Bioaccumulation Potential: No data available.

SECTION 13: Disposal considerations

General Information: Dispose of waste and residues in accordance with local authority requirements.

Disposal Methods: Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local Regulations.

SECTION 14: Transport information

Non-bulk packaging's (capacity less than or equal to 119 gallons) Not regulated

Transported by air or marine vessel: Bulk or non-bulk packaging's

UN1993, Flammable Liquid,

N.O.S. (Naphtha Solvent), 3, PG

III, ERG #128

**SECTION 15: Regulatory information**

Canadian Controlled Products Regulations: This product has been classified according to the hazard criteria of the Canadian Controlled Products Regulations, Section 33, and the MSDS contains all required information.

WHMIS Classification: D2B

Inventory Status:

This product or all components are listed or exempt from listing on the following inventory: **DSL, TSCA**

US Regulations

CERCLA Hazardous Substance List (40 CFR 302.4): **Not regulated.**

SARA Title III

Section 302 Extremely Hazardous Substances (40 CFR 355, Appendix A): Not regulated.

SARA 313

As of the preparation date, this product did not contain a chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

NFPA 704 Hazard Codes - - - - - Signals Health: 0

Flammability: 1

Reactivity: 0 Special Hazards: -

Section 311/312 (40 CFR 370):

X	Acute (Immediate)
	Chronic (Delayed)
	Fire
	Reactive

Section 313 Toxic Release Inventory (40 CFR 372):

Chemical Name	CAS-No.	Reporting threshold for other users	Reporting threshold for manufacturing and processing
Aluminum nitrate	7784-27-2	10000 lbs.	25000 lbs.
Aluminum oxide	1344-28-1	10000 lbs.	25000 lbs.

For reporting purposes: the De Minimis Concentration for a toxic chemical in a mixture is 0.1% for carcinogens as defined in 29 CFR 1910.1200(d)(4) or 1% for others.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Not regulated.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3): Not regulated.

Drug Enforcement Act: Not regulated.

TSCA

TSCA Section 4(a) Final Test Rules & Testing Consent Orders: Not regulated.

TSCA Section 5(a) (2) Final Significant New Use Rules (SNURs) (40CFR 721, Subpt. E): Not regulated.

TSCA Section 5(e) PMN-Substance Consent Orders: Not regulated.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

**State Regulations****California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):** Not regulated.**Massachusetts Right-To-Know List:** Aluminum oxide; Distillates (petroleum), hydro treated light naphthenic**Michigan Critical Materials List (Michigan Natural Resources and Environmental Protection Act (Act. 451 of 1994)):**

Not regulated.

Minnesota Hazardous Substances List: Aluminum oxide; Aluminum nitrate**New Jersey Right-To-Know List:** Aluminum oxide; Aluminum nitrate**Pennsylvania Right-To-Know List:** Aluminum oxide; Aluminum nitrate**Rhode Island Right-To-Know List:** Aluminum oxide**SECTION 16: Other information**

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

NFPA Hazard Classification

	Health Hazard	Fire Hazard	Instability	Special Hazard
NFPA	1	0	0	--

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe

NFPA Label colored diamond code: Blue - Health; Red - Flammability; Yellow - Instability; White - Special Hazards

	Health Hazard	FLAMIBILITY	PHYSICAL HAZARD	PERSONAL PROTECTION
HMIS	1	0	0	X

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; - Severe Personal Protection codes: X - Specialized Handling

HMIS Label colored bar code: Blue - Health; Red - Flammability; Orange - Physical Hazards; White - Special

Issue Date: September 20, 2016**Supersedes****Date:** 3-1-2012

DISCLAIMER: The information in this SAFETY DATA Sheet (SDS) is believed to be correct as of the date issued. Azuradisc **MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.** User is responsible for determining whether the Azuradisc product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Azuradisc product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Azuradisc product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Azuradisc provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Azuradisc makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information available directly from Azuradisc Inc.